



# Technical Data

## Submersible Pump - GST 55-22

Revision no.

Page:

1

Receiver

From

Company name  
Respons. Department  
Person in charge  
Phone number  
Fax no  
E-mail address




**Brand: Gol Pumps**  
**Model: GST 55-22**

**Weight (lb)**

| Pump | Motor | Pump + Motor |
|------|-------|--------------|
| 29.3 | 64    | 93.3         |

**Cable**

| Length (Ft) | AWG |
|-------------|-----|
| 8.2         | 14  |

**Dimensions:**

| Outlet | Motor Dia. | Dimensions (inch) |    |      |       |
|--------|------------|-------------------|----|------|-------|
|        |            | A                 | B  | C    | D     |
| NPT 2" | 4"         | 55.5"             | 2" | 3.9" | 83.2" |

Project

Project ID

Created by

Created on

Last update



# Performance Curves

## Submersible Pump - GST 55-22

Revision no.

Page:


2

Receiver

From

Company name  
Respons. Department  
Person in charge  
Phone number  
Fax no  
E-mail address

| Pump Model | Motor |     | Q Capacity 3500RPM |     |      |      |      |      |     |      |      |      |     |      |      |     |      |
|------------|-------|-----|--------------------|-----|------|------|------|------|-----|------|------|------|-----|------|------|-----|------|
|            |       |     | Gal/Min            | 0   | 21.1 | 23.8 | 26.4 | 31.7 | 37  | 42.3 | 47.6 | 52.8 | 58  | 63.4 | 68.7 | 74  | 79.3 |
|            | kW    | HP  | Head in Feet       | 627 | 555  | 545  | 532  | 512  | 489 | 459  | 430  | 387  | 348 | 299  | 246  | 180 | 115  |
| GST 55-22  | 5.5   | 7.5 |                    |     |      |      |      |      |     |      |      |      |     |      |      |     |      |



Project

Project ID

Created by

Created on

Last update



## Part List and Materials

### Submersible Pump - GST 55-22

Revision no.

Page:


3

Receiver

From

Company name  
Respons. Department  
Person in charge  
Phone number  
Fax no  
E-mail address

| Motor Model | P2  |     | S.F  | Voltage | Phase | In   | Imax | Istart | PF (%)         |                 | Efficiency (%) |                 | RPM  | Thrust |
|-------------|-----|-----|------|---------|-------|------|------|--------|----------------|-----------------|----------------|-----------------|------|--------|
|             | kW  | HP  |      | V       | PH    | A    | A    | A      | Allowable Load | Overload Factor | Allowable Load | Overload Factor |      | N      |
|             |     |     |      |         |       |      |      |        |                |                 |                |                 |      |        |
| 4CS6396     | 5.5 | 7.5 | 1.15 | 460     | Three | 10.9 | 12.1 | 78.3   | 0.79           | 0.83            | 79.1           | 78.7            | 3450 | 6000   |



| No. | Part Name                  | Materials                  |
|-----|----------------------------|----------------------------|
| 1   | Discharge Head             | AISI 304                   |
| 4   | Check Valve Cone           | AISI 304                   |
| 6   | Check Valve Retaining Ring | AISI 304                   |
| 8   | Bearing Spider             | Glass Filled Polycarbonate |
| 12  | Diffuser                   | Glass Filled Polycarbonate |
| 13  | Bowl                       | AISI 304                   |
| 18  | Impeller                   | Noryl                      |
| 34  | Strainer                   | AISI 304                   |
| 40  | Pump Shaft / Coupling      | AISI 304                   |
| 42  | Shaft Sleeve               | AISI 304 or Norly          |
| 48  | Pump Casing                | AISI 304                   |
| 52  | Cable Guard                | AISI 304                   |
| 86  | O-Ring                     | NBR                        |
| 92  | Bearing                    | Polyacetal                 |

Project

Project ID

Created by

Created on

Last update