



Technical Data

Submersible Pump - GSP 40-30

Revision no.

Page:

1

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address




Brand: Gol Pumps
Model: GSP 40-30

Weight (lb)

Pump	Motor	Pump + Motor
37	68.7	105.7

Cable

Length (Ft)	AWG
11.5	4x14

Dimensions:

Outlet	Motor Dia.	Dimensions (inch)		
		A	B	C
NPT 2"	4"	57.4"	84.8"	3.9"

Project

Project ID

Created by

Created on

Last update



Performance Curves

Submersible Pump - GSP 40-30

Revision no.

Page:


2

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Pump Model	Motor		Q Capacity 3450RPM									
	P2		G/Min	0	21.1	23.8	26.4	31.7	37	42.3	47.6	52.8
	kW	HP	Head in Feet	823.5	721.8	705.4	692.3	669.3	639.8	597.1	538.1	456
GSP 40-30	7.5	10										



Project

Project ID

Created by

Created on

Last update



Part List and Materials

Submersible Pump - GSP 40-30

Revision no.

Page:

3

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Motor Model	P2		S.F	Voltage	Phase	In	In (SF)	Is/In	Cs/Cn	P1	Cos ϕ	η %	RPM
	kW	HP		V	PH	A	A			W			
4GG	7.5	10	1.15	460	Three	15.4	16.6	7.1	3.9	9300	0.78	80	3450


SF: Service factor

Is/In: Locked rotor current/Rated current

Cos ϕ : Power factor

In: Rated current

Cs/Cn: Locked rotor torque/Rated torque

 η : Efficiency

Pos.	Part Name	Materials
01	Discharge	AISI 316
12	Diffuser	AISI 316
18	Impeller	AISI 316
21	Split Cone	AISI 316
22	Split Cone Nut	AISI 316
24	Stop Ring	Carbon + Graphite + PTFE
32	Neck Ring Retainer	AISI 316
34	Strainer	AISI 316
36	Suction Interconnector	AISI 316
37	Coupling	AISI 316
40	Pump Shaft	AISI 316
47	Strap	AISI 316
52	Cable Guard	AISI 316
87	Neck Ring	AISI 316 + HNBR
88	Nut	AISI 316
89	Bearing	HNBR

Project

Project ID

Created by

Created on

Last update