



Technical Data

Submersible Pump - GST 25-26

Revision no.

Page:

1

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address




Brand: Gol Pumps
Model: GST 25-26

Weight (lb)

Pump	Motor	Pump + Motor
17.8	55	72.8

Cable

Length (Ft)	AWG
8.2	14

Dimensions:

Outlet	Motor Dia.	Dimensions (inch)			
		A	B	C	D
NPT 1 1/2"	4"	34	1 1/2	3.9	55.7

Project

Project ID

Created by

Created on

Last update



Performance Curves

Submersible Pump - GST 25-26

Revision no.

Page:

2

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Pump Model

Motor

Q Capacity 3500RPM

Gal/Min

0

13.2

15.9

18.5

21.1

23.8

26.4

31.7

kW

HP

Head in

Feet

768

702

676

643

600

554

499


454

409

GST 25-26

3.7

5



Project

Project ID

Created by

Created on

Last update



Part List and Materials

Submersible Pump - GST 25-26

Revision no.

Page:


3

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

Motor Model	P2		S.F	Voltage	Phase	In	Imax	Istart	PF (%)		Efficiency (%)		RPM	Thrust
	kW	HP		V	PH	A	A	A	Allowable Load	Overload Factor	Allowable Load	Overload Factor		N
4CS6376	3.7	5	1.15	460	Three	8.7	9.5	68.4	0.68	0.72	77.4	77.9	3450	6000



No.	Part Name	Materials
1	Discharge Head	AISI 304
4	Check Valve Cone	AISI 304
6	Check Valve Retaining Ring	AISI 304
8	Bearing Spider	Glass Filled Polycarbonate
12	Diffuser	Glass Filled Polycarbonate
13	Bowl	AISI 304
18	Impeller	Noryl
34	Strainer	AISI 304
40	Pump Shaft / Coupling	AISI 304
42	Shaft Sleeve	AISI 304 or Norly
48	Pump Casing	AISI 304
52	Cable Guard	AISI 304
86	O-Ring	NBR
92	Bearing	Polyacetal

Project

Project ID

Created by

Created on

Last update